

Product data sheet

Center heating system cleaner 500ml



Product code - 609940

High concentrate chemical cleaner specially designed to remove central heating system sludge and debris, while protecting vulnerable system metals during cleaning. Formulated to clean a typical 100 litre/ten radiator system.



Features

- High performance chemical cleaner
- Removes sludge, debris and scale
- Restores heating efficiency of existing systems
- Treats 100 litres
- Suitable for all heating systems and water types
- Compatible with all metals including aluminium

Specification

Appearance	Liquid
Colour	Brown
Odour	Slight
Solubility	Soluble in water
pH (concentrated solution)	6.0-7.0
Relative density	1.03-1.09 g/cm ³



Plumbing

Heating

Cooling

Drainage

Pipe

Parts

WOLSELEY



The Specialist Merchant

Product uses

For the removal of system sludge, debris and scale from existing heating systems, restoring heating efficiency. Removes corrosion from all metals and alloys commonly found in heating systems including mild steel, copper, aluminium and their alloys. Compatible with all rubbers and other non-metallic components.

How to use

500ml of Center central heating system cleaner will provide effective treatment for a typical 100 litre/ten radiator system.

Introduce Cleaner to the system via the filling loop or radiator using a suitable injector, or via a filter. For open vented systems cleaner can be added via the Feed & Expansion (F&E) tank, remembering to remove sufficient water via the drain-point to ensure cleaner enters the system circuit.

Clean and flush the system as recommended in BS7593. Following the system cleanse, drain and flush thoroughly until the water runs clear. Refill the system and add the correct dosage of Inhibitor for the optimum protection against the build-up of corrosion and limescale.

Cleaner should be circulated in the system for a minimum of 1 hour and can be left in the system for a maximum of 7 days.

Application

Center central heating system cleaner is suitable for all sealed and open vented central heating systems in accordance with BS7593. Cleaner is not suitable for use in single feed indirect 'primatic' cylinders where potable water treatment is required.

Environmental

Center central heating system cleaner is classified as non-hazardous and while delivering effective protection against corrosion and limescale is non-toxic and biodegradable.

Packaging, handling and storage

Available in 500ml plastic containers.

Non-hazardous, but as for all domestic chemicals, avoid direct contact with the liquid, keep out of reach of children and avoid contact with eyes and skin. Store in a cool, well ventilated area. Keep container tightly closed. Must only be kept in original packaging.

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of products and so reserve the right to change specifications without prior notice.

Version number 1



Plumbing

Heating

Cooling

Drainage

Pipe

Parts